

FACT SHEET

# 48 V Battery pack



**Battery packs by ElringKlinger based on cylindrical cells:**  
Powering the pulse of e-mobility.

**The lithium-ion battery pack from ElringKlinger represents a 48 V setup for traction batteries.**

The certified pack meets the most demanding safety requirements that apply in the automotive industry so it can also be used in off-highway applications such as industrial trucks, leisure applications or stationary storage units.

## Technology

- » Battery junction box (BJB), communication interface: three CAN channels, monitoring abilities: SoC, SoH, SoF. Safety functions: over-current protection, cell over- and undervoltage protection, over-temperature protection. PEU (Pressure Equalizing Unit). FuSi level: ASIL B
- » Passive cooling
- » Interface (traction, LV) to vehicle: diagnostic- and drive-information via CAN (Controlled Area Network), IL (Integrated Logic), Master-Slave-Option
- » Production-ready assembly technology

**ELRINGKLINGER – YOUR PARTNER  
FOR E-MOBILITY SOLUTIONS WITH  
BATTERY TECHNOLOGY**

Cell Expertise – Module and Pack Design –  
Installation Space Optimization – Simulation and  
Testing – Certification – Prototyping – Process  
Engineering – Industrialization – Integrated Solutions  
and Components – Recycling

# Parameters

- » 48 V pack based on standard ElringKlinger modules (1S2P)
- » ElringKlinger standard modules based on cylindrical cells (12S48P)
- » Connection in parallel possible to increase the capacity
- » Connection in series possible to increase the voltage level

# Benefits

- » Maximum reliability due to functional integration (CSC, BJB, PEU)
- » Full pack supply
- » High number of charge/discharge cycles
- » High continuous discharge current
- » Easy integration

# Specifications

## 1s2p BATTERY PACK

<b>CELL TECHNOLOGY</b>	Lithium-ion (NMC)
<b>CELL TYPE</b>	21700 cylindrical cells
<b>PACK SET UP</b>	12s 48p (2P)
<b>DIMENSIONS (MM)</b>	1200 x 670 x 210
<b>WEIGHT (KG)</b>	141
<b>MECHANICAL INTERFACE</b>	12 x M10
<b>NOMINAL VOLTAGE PACK (V)</b>	44.3
<b>NOMINAL CAPACITY (AH)</b>	474
<b>NOMINAL ENERGY (KWH)</b>	20.9
<b>NOMINAL SPECIFIC ENERGY (WH/L)</b>	358 (module basis)
<b>NOMINAL GRAVIMETRIC ENERGY (WH/KG)</b>	207.5 (module basis)
<b>MAX. CONTINUOUS CHARGE (A / C-RATE / KW)</b>	250 / 0.5 / 11
<b>MAX. CONTINUOUS DISCHARGE (A / C-RATE / KW)</b>	550 / 1.2 / 24.4
<b>MAX. PULSE DISCHARGE CURRENT (60S) (A / C-RATE / KW)</b>	700 / 1.5 / 31
<b>OPERATING TEMPERATURE (°C)</b>	Operating temperature cells: -20 to +55
<b>THERMAL MANAGEMENT</b>	Passive cooled
<b>COMMUNICATION INTERFACE</b>	CAN
<b>ELECTRICAL INTERFACE</b>	6 x M6 (DC+/-)
<b>SAFETY FEATURES</b>	Pressure Equalizing Unit, Fire-resistant Steel Housing, Hydrogen Gas Sensor, Temp. Sensor, ASIL-B Certificate, Bond wire fuse, central fuse
<b>LIFE-TIME (UNTIL 80% CAPACITY)</b>	> 1,000 cycles / depending on operating Strategy & DoD
<b>CONFORMITY</b>	UN 38.3, ECE R10, ECE R100

### YOUR CONTACT

ElringKlinger AG  
E-mail: [info@elringklinger.com](mailto:info@elringklinger.com)

**ElringKlinger AG** | Daimlerstr. 6-8 | 72639 Neuffen | Germany  
[www.elringklinger.com](http://www.elringklinger.com)

The information provided in this document is the result of technological analyses and may be subject to changes depending on the design of the system. We reserve the right to make technical changes and improvements. The information is not binding and does not represent warranted characteristics. We do not recognize any claims for compensation based on this information. We accept no liability for printing errors.



02/26

### ▶ **SHAPE**<sup>30</sup>

The strategic direction of  
the ElringKlinger Group

